



**NBS SPECIFICATION FOR
FIX TO TIMBER BUDGET 407
10MM HOLLOW FORM OUTDOOR HOARDING PANEL - 01.10.16**

K11 Rigid sheet flooring/ sheathing/ decking/ sarking/ linings/ casings

TYPE OF HOARDING

- 112 RE-LOCATABLE HOARDING SYSTEM: KK Ultraspan
- Hoarding type: Temporary
 - Hoarding System:
 - Supplier: **Hoarding Warehouse Limited**
10-14 Ward Street, Bradford, West Yorkshire, BD7 3PR
Telephone: 0845 058 4999 Email: info@hoardingwarehouse.co.uk
www.hoardingwarehouse.co.uk
 - Product reference: **Fix to Timber Budget 407**
 - Panel Type: Extruded PVC
 - Panel Thickness: 10mm
 - Panel Widths: 407mm
 - Panel Material Source: Recycled
 - Colour: White | Grey | bespoke colours on request
 - Fixings: Consult with Manufacturer, identifying hoarding height
 - Partition height: As drawings 2500mm | 3000mm | 4000mm
 - Partition abutments:
 - Deflection allowance: To Structural Engineer's Recommendation.
 - Partition joints:
 - Pelmet Detail
 - Skirt Detail
 - Vertical: Interlocking Panels
 - 90 Degree Corners: 50mm Corner Flashing
 - Non-90 Degree Corners: Flexi Angle
 - Accessories: Flexi Angle at Window Reveals / Openings.

INSTALLATION

- 410 WORKMANSHIP GENERALLY
- Setting out: Plumb, true to line and level, and free from bowing, undulations and other planar distortions.
 - Joints: Align accurately with no lipping.
 - Stability: Fix securely to timber frame (posts and rails) with screws or nails
 - Moisture and thermal movement of framing/ panels: Make adequate allowance.
- 425 INSTALLING RE-LOCATABLE HOARDINGS
- Site dimensions: Check before installation. Give notice of discrepancies.
 - Perimeter abutments: Accommodate deviations whilst maintaining partition system performance. Form make up/ closer pieces accurately around projections and features.
 - Customisation: Do not cut or otherwise alter framing/ panels on site, except where shown on drawings.
 - Intermediate joints in exposed frame members and trims: Keep to a minimum.