



**NBS SPECIFICATION FOR  
FIX TO TIMBER SHEET 1200  
3MM SHEET OUTDOOR HOARDING PANEL - 01.10.16**

**K11 Rigid sheet flooring/ sheathing/ decking/ sarking/ linings/ casings**

**TYPE OF HOARDING**

**112 RE-LOCATABLE HOARDING SYSTEM: FIX TO TIMBER SHEET 1200**

- Hoarding type: Temporary
- Hoarding System:
  - Supplier: **Hoarding Warehouse Limited**  
10-14 Ward Street, Bradford, West Yorkshire, BD7 3PR  
Telephone: 0845 058 4999 Email: [info@hoardingwarehouse.co.uk](mailto:info@hoardingwarehouse.co.uk)  
[www.hoardingwarehouse.co.uk](http://www.hoardingwarehouse.co.uk)
  - Product reference: **3mm Sheet**
  - Panel Thickness: 3mm
  - Panel Widths: 1200mm
  - Colour: White | Black | Medium Grey | Dark Grey | Light Blue | Dark Blue | Silver | Red | Green | Yellow | Cream | Burgundy. Bespoke colours on request
  - Fixings: Consult with Manufacturer, identifying hoarding height
- Partition height: 2400mm
- Partition abutments:
  - Deflection allowance: To Structural Engineer's Recommendation.
- Partition joints:
  - Skirt
  - Pelmet
  - Vertical: Interlocking Panels
  - 90 Degree Corners: 50mm Corner Flashing
  - Non-90 Degree Corners: Flexi Angle
- Accessories: Flexi Angle at Window Reveals / Openings.

**INSTALLATION**

**410 WORKMANSHIP GENERALLY**

- Setting out: Plumb, true to line and level, and free from bowing, undulations and other planar distortions.
- Joints: Align accurately with no lipping.
- Stability: Fix securely to timber frame (posts and battens) with screws or nails
- Moisture and thermal movement of framing/ panels: Make adequate allowance.

**425 INSTALLING RE-LOCATABLE HOARDINGS**

- Site dimensions: Check before installation. Give notice of discrepancies.
- Perimeter abutments: Accommodate deviations whilst maintaining partition system performance. Form make up/ closer pieces accurately around projections and features.
- Customisation: Do not cut or otherwise alter framing/ panels on site, except where shown on drawings.
- Intermediate joints in exposed frame members and trims: Keep to a minimum.